





## **Drawings & Terminal Position**



#### ODS-AGM30L **RIGHT POSITIVE FEMALE TERMINAL**



#### Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

# **Charging and Self-Discharge**

Cyclic Charge Voltage 14.4 - 14.8V @ 25°C Float Charge Voltage 13.5 - 13.8V @ 25°C Charger voltage at 68°F (20°C) 14.4V to 14.8V Self-discharge per month at 68°F (20°C) 1.25% Self-discharge per month at 104°F (40°C) 5%



Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

EnerSys Asia No. 85, Tuas Avenue 1 Singapore 639518 Tel: +65 6558 7333

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

### ODS-AGM30L

#### **Battery Type**

- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle

#### **Power and Performance**

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	720A
Cold Cranking Amps (CCA)	400A
HCA	575A
MCA	500A
20Hr Nominal Capacity (Ah)	30Ah
10Hr Nominal Capacity (Ah)	27Ah
Reserve Capacity Minutes	50 mins
Terminal	M6 Receptacle
Torque Spec in-lbs (Nm max)	50 (5.6)
Recommended Min. Charging Current (A)	2.7A
UPC	635241142372

#### **Dimensions and Weight**

Length 6.6 in / 168 mm Width 4.9 in / 124 mm Height (terminals included) 6.9 in / 175 mm Height (container) 6.9 in / 175 mm Weight 20 lbs / 9.1 kg

#### **Temperature**

Operating temperature range  $-40^{\circ}F/-40^{\circ}C$  to  $140^{\circ}F/+60^{\circ}C$ Optimum storage temperature 68°F / +20°C

#### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

\*Cold Start Performance S.A.E J537 Apr 2016