




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

| | |
|--|---------------------|
| Cyclic Charge Voltage | 14.4 - 14.8V @ 25°C |
| Float Charge Voltage | 13.5 - 13.8V @ 25°C |
| Charger voltage at 68°F (20°C) | 14.4V to 14.8V |
| Self-discharge per month at 68°F (20°C) | 1.25% |
| Self-discharge per month at 104°F (40°C) | 5% |

80% depth of discharge cycles



EnerSys World Headquarters
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-800-964-2837

EnerSys EMEA
EH Europe GmbH
Baarerstrasse 18
6300 Zug, Switzerland

EnerSys Asia
No. 85, Tuas Avenue 1
Singapore 639518
Tel: +65 6558 7333

Want more info?
Scan code to access
the ODYSSEY[®] Battery
Literature Library



ODX-AGM78

(78-PC1500)

Battery Type

- Group 78 with 3/8 inch threaded side receptacles
- Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

| | |
|---|--------------|
| Voltage | 12V |
| Pulse (5 second) Hot Cranking Amps (PHCA) | 1500A |
| Cold Cranking Amps (CCA) | 850A |
| HCA | 1250A |
| MCA | 1050A |
| 20Hr Nominal Capacity (Ah) | 68Ah |
| 10Hr Nominal Capacity (Ah) | 62Ah |
| Reserve Capacity Minutes | 135 mins |
| Terminal | Side |
| Torque Spec in-lbs (Nm max) | 60 (6.8) |
| Internal Resistance (mΩ) | 2.5 mΩ |
| Short Circuit (A) | 3100A |
| Recommended Min. Charging Current (A) | 6.2A |
| UPC | 635241140439 |

Dimensions and Weight

| | |
|-----------------------------|--------------------|
| Length | 10.9 in / 277 mm |
| Width | 6.8 in / 173 mm |
| Height (terminals included) | 7.3 in / 185 mm |
| Height (container) | 7.3 in / 185 mm |
| Weight | 49.5 lbs / 22.4 kg |

Temperature

| | |
|-----------------------------|--------------------------------|
| Operating temperature range | -40°F / -40°C to 176°F / +80°C |
| Optimum storage temperature | 68°F / +20°C |

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016