



## GS Scheda Tecnica

### GS SMF053 - GS SMF Battery

#### Prestazione

Tensione	12V
Capacità (20 ore)	45Ah
Corrente di spunto A (EN1)	400A

#### Dimensioni

Lunghezza	238mm
Profondità	129mm
Altezza	224mm

#### Pesi e Misure

#### Caratteristiche del Monoblocco

Tipo di monoblocco	JIS B24
Fissaggi alla base	N
Indicatore dello stato di carica	✓
Maniglie	✓
Circuito di sfiato	✓

#### Tecnologia


Pastiglia antideflagrante	✓
Tecnologia	Ca/Ca
Separatore	PE
Corrente di carica raccomandata	3A
Performance Marking	W4-C2-V2-E1




#### Tipologia dei terminali

##### T1/T3


Standard DIN Post



Remove T1 adapter for T3



#### Schema di Collegamento



#### Fissaggio batteria



Scheda tecnica prodotta su E&OE



## GS Technical Data Sheet

### GS SMF053 - GS SMF Battery

#### Performance

Voltage	12V
Capacity (20-hour)	45Ah
Cold Cranking Amps (EN1)	400A

#### Dimensions

Length	238mm
Width	129mm
Height	224mm

#### Weights & Measures

#### Container Features

Case Type	JIS B24
Hold Down	N
State of Charge Indicator	✓
Handles	✓
End Venting	✓

#### Technology


Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
Recommended Charge Rate	3A
Performance Marking	W4-C2-V2-E1




#### Terminal Type

##### T1/T3


Standard DIN Post



Remove T1 adapter for T3



#### Cell Assembly Layout



#### Battery Hold-down



Data Sheet generated on 18/10/2024 - E&OE